

Gas Detector

For Toxic Gas

Model No. GD-2700-LCD (Non-explosion proof Type)



"Innovator in Gas Detection"

Gas Detector (GD-2700-LCD)



■ Feature

- * Local LCD Digital Display
- * High Reaction Speed and High Accuracy
- * Reliability (Long Life, High Sensitivity, Selectivity, Stability, Reappearance).
- * Minimized Interference by Electric Noise, Temperature, Humidity & Pressure.
- * 4-20mA Output for transmission
- * Water-proof and Dustproof Structure
- * Non-corrosive Housing

■ Products Information

GD-2700-LCD

Gas Detector

For Toxic Gas (Non-explosion proof Type)



■ Specifications

Gas Detector (GD-2700-LCD)

Model Number	GD-2700-LCD
Type	Diffusion type
Detection Principle	Electro-chemical Type/Galvanic Cell Type
Measuring Gas	Toxic Gas
Output Signal	4-20mA DC
Power Supply	DC 21V ~ DC 27V
Operating Temp. & Humid.	-20℃ ~ +50℃, 95%(RH)
Accuracy	±3% Full Scale
Measuring Range	ppm
Telemetry Line	Within 2.5 km
Display	Local LCD Digital Display
Cable	CWS 1.25 x 2 wire Shield
Conduit Opening	1/2" or 3/4" PF NPT
Case Material	IP 65 (poly carbonate housing)
Weight	aaprox. 1.0 kg
Dimension	148 X 75 X 75 mm
Mounting Type	Wall Mounting

Distributed by :



G · E · T

Gas Detection Electronics Co., Ltd.

#1108, Daeryung Bldg., Mullaedong-5 ga,
Yeongdeungpo-gu, Seoul, 150-958, Korea

TEL : +82-2-6093-1910

FAX : +82-2-6093-1911

E-mail : info@gasdetection.co.kr

Website : www.gasdetection.co.kr